



WITH APPROVED COUPLING BANDS. HDPE APRON END SECTIONS ARE NOT ALLOWED.

NOTE: MINIMUM DIAMETER OF CULVERT IS 15 INCHES, UNLESS THE DITCH IS TOO SHALLOW, IT COULD POSSIBLY BE 12 INCH. THIS IS UP TO THE DISCRETION OF THE ROAD AUTHORITY. LENGTH OF CULVERT TO ACCOMMODATE 4:1 SLOPE ON EACH SIDE OF THE DRIVEWAY WITH STEEL APRONS AND A MINIMUM OF 12 INCHES OF TOP COVERAGE, *UNLESS THE DEPTH OF THE DITCH DOES NOT ALLOW. AT THE DISCRETION OF THE ROAD AUTHORITY.*

NOTE: DRIVEWAY SHALL BE GRAVEL WITH TOP 6 INCHES BE CLASS 5 GRAVEL. *NO ORGANIC MATERIAL, DRIED CONCRETE WASTE OR ANY OTHER SUBSTANCE PROHIBITED BY THE MINNESOTA POLLUTION CONTROL AGENCY MAY BE USED.*

Oliver Surveying & Engineering, Inc.

Land Surveying – Civil Engineering- Land Planning
 580 Dodge Ave. Elk River, MN 55330
 763-441-2072

Date: 04/06/14

RESIDENTIAL
 DRIVEWAY CULVERT DETAIL
 MILO TOWNSHIP

Updated: 08/16/22 MILO-R-DWC.DWG